

InfiLINK XG Xm/3X.500.2x500.2x22


2990-4010 MHz

Description	InfiLINK XG Xm/3X.500.2x500.2x22, 3 GHz point-to-point unit, net throughput up to 500 Mbps, integrated dual-pol antenna, 22 dBi, 12x12 deg
Performance	up to 500 Mbps
Recommended distances	up to 30 km
Radio technology	MIMO 2x2, Cyclic single carrier
Modulation types	from QPSK 1/4 to QAM256 30/32
Transmit power	up to 27 dBm
Receiver sensitivity	down to -88 dBm
Frequency range	2990-4010 MHz
Channel width	10, 20, 40 MHz
Center frequency adjustment step	1 MHz
Duplex scheme	TDD, Hybrid-FDD
Antenna	22 dBi
Wired Interfaces	2x GigabitEthernet, SFP



InfiLINK XG Xm/3X.500.2x500.2x22

2990-4010 MHz

Consumption	up to 30 W
Power options	90-240 VAC ~ @ 50/60 Hz 43..56 VDC, 802.3at compliant
Outdoor Unit (ODU)	371 x 371 x 89 mm, 3.3 kg
	



InfiLINK XG Xm/3X.500.2x500.2x22

2990-4010 MHz

Features

RADIO

- ▶ **Best-in-breed spectral efficiency**
 - up to 14 bps/Hz
 - real throughput in excess of 130 Mbps in just 10 MHz of spectrum
- ▶ **High transmit power and perfect sensitivity even at the highest-order modulations**
 - Reliable signal receiving in both LOS and NLOS conditions
- ▶ **TDD synchronization using a built-in GNSS receiver**

NETWORKING

- ▶ **Built-in full-fledged L2 switch supporting VLAN and STP**
- ▶ **Transparent L2 transport for Ethernet traffic of any type**
- ▶ **Timing transport using precision time protocol (IEEE 1588v2) support**
 - transparent clock mode supported

MANAGEMENT FEATURES

- ▶ **Web-based graphical user interface**
- ▶ **Command line interface**
- ▶ **SNMP v1/2c/3 support (MIB-II and proprietary MIBs)**
- ▶ **Centralized monitoring using EMS InfiMONITOR.**

QUALITY-OF-SERVICE

- ▶ **QoS support:**
 - 4 priority queues: strict and weighted prioritisation
 - Classification based on IEEE 802.1p
 - Egress rate limiting on each network port

INSTALLATION AND DIAGNOSTIC TOOLS

- ▶ **LED indication**
 - power status
 - wired and wireless link status
 - received signal strength indication
 - TDD sync status
- ▶ **Web GUI tools**
 - antenna alignment tool
 - spectrum analyzer



InfiLINK XG Xm/3X.500.2x500.2x22

2990-4010 MHz

Features

ENVIRONMENTAL

- ▶ **Outdoor unit:**
 - Operating temperature range $-40..+60^{\circ}\text{C}$
 - IP66/IP67 compliant water and dust protection
- ▶ **Indoor unit**
 - 90-240 VAC ~ @ 50/60 Hz or $\pm 43.. \pm 56$ VDC, 802.3at compliant
 - Power consumption up to 30 W

STANDARD COMPLIANCE

- ▶ **Safety:**
 - EN 60950-1:2006, UL 60950-1 2nd ed.
- ▶ **Radio:**
 - EN 301 893 v.1.8.1, EN 302 502, v.1.2.1, FCC part 15.247
- ▶ **EMC:**
 - ETSI EN 301 489-1, ETSI EN 301 489-17, FCC Part 15 Class B
- ▶ **RoHS:**
 - Directive 2002/95/EC

