

InfiMAN 2x2 R5000-Mmxb/38.300.2x200.2x14


3700-3900 MHz

Description	InfiMAN 2x2 R5000-Mmxb/38.300.2x200.2x14, 3 GHz base station sector, net throughput up to 240 Mbps, integrated dual-pol sectorial antenna, 14 dBi, 90x8 deg
Performance	up to 240 Mbps
Recommended distances	up to 20 km
Radio technology	MIMO 2x2 (OFDM 64/128)
Modulation types	from BPSK 1/2 to QAM64 5/6
Transmit power	up to 23 dBm
Receiver sensitivity	down to -98 dBm
Frequency range	3700-3900 MHz
Channel width	3.5, 5, 7, 10, 14, 15, 20, 28, 30, 40 MHz
Center frequency adjustment step	125 kHz
Duplex scheme	TDD
Antenna	14 dBi
Wired Interfaces	GigabitEthernet



InfiMAN 2x2 R5000-Mmxb/38.300.2x200.2x14

3700-3900 MHz

Consumption	up to 12 W					
Power options	110-240 VAC @ 50/60 Hz ±43..56 VDC					
Outdoor Unit (ODU)	371 x 371 x 90 mm, 3.4 kg					
						
Part Number Options	Prefix	Freq. Band	Bitrate	Output Power	Ant.	Capacity
	<i>R5000-Mmxb</i>	<i>38</i>	<i>300</i>	<i>2x200</i>	<i>2x14</i>	<i>300</i>
Part Number Example	R5000-Mmxb/38.300.2x200.2x14					



InfiMAN 2x2 R5000-Mmxb/38.300.2x200.2x14

3700-3900 MHz

Features

RADIO

- ▶ Voice/RTP Aware Superpacketing
- ▶ DFS
- ▶ Automatic Bitrate Control
- ▶ Automatic Transmit Power Control
- ▶ Automatic Distance Learning
- ▶ Channel Time Adjustment
- ▶ Spectrum Analyzer mode
- ▶ Channel testing tools

NETWORKING

- ▶ Ethernet-over-IP and IP-over-IP tunneling
- ▶ ARP protocol support
- ▶ MAC/IP filtering
- ▶ Full-fledged 2nd layer switch
- ▶ RIPv2 / OSPFv2 /static routing
- ▶ L2/L3 Firewall
- ▶ NAT (multipool, H.323-aware)
- ▶ DHCP client/server/relay

MANAGEMENT FEATURES

- ▶ Various Management Protocols: HTTP, telnet, SNMP v1/2c/3 (MIB-II and proprietary MIBs)
- ▶ Graphical User Interface
- ▶ LED Indication: power status, wireless and wired link status, signal level
- ▶ Antenna alignment tool
- ▶ Automatic software update
- ▶ Online monitoring with proprietary EMS InfiMONITOR.

QUALITY-OF-SERVICE

- ▶ 17 priority queues
- ▶ IEEE 802.1p support
- ▶ IP TOS / DiffServ support
- ▶ Full voice support
- ▶ Traffic limiting (absolute, relative, mixed)
- ▶ Traffic redirection



InfiMAN 2x2 R5000-Mmxb/38.300.2x200.2x14

3700-3900 MHz

Features

ENVIRONMENTAL

- ▶ **Outdoor Units: -40..+60C, 100% humidity, condensing**
- ▶ **Indoor Unit: 0..+40C, 95% humidity, non-condensing**

SECURITY FEATURES

- ▶ **Storm/flood protection**
- ▶ **Password protection**
- ▶ **Secure command-line access via SSH protocol**

MAC

- ▶ **Dynamic adaptive polling:**
 - Centralized marker grant mode
 - Dynamically takes into account channel activity
 - Permanent channel testing
- ▶ **Pseudo-radio interface:**
 - unique InfiNet Wireless feature to join InfiNet networks via 3rd party equipment
- ▶ **Automatic over-the-air firmware upgrade**

STANDARD COMPLIANCE

- ▶ **Radio**
 - EN 301 893 v.1.7.1
 - EN 302 502 v.1.2.1
 - FCC part 15.247
- ▶ **EMC**
 - EN 301 489-1
 - EN 301 489-17
 - FCC Part 15 Class B
- ▶ **Safety**
 - ETSI EN 60 950-1:2006
- ▶ **RoHS**
 - Directive 2002/95/EC

