


InfiMAN 2x2 R5000-0mxb/35.300.2x200

Description	InfiMAN 2x2 R5000-0mxb/35.300.2x200, 3 GHz base station sector, net throughput up to 250 Mbps, 2x N-type (F) connectors for external antenna
Net throughput	up to 250 Mbps
Recommended distances	up to 25 km
Radio technology	MIMO 2x2 (OFDM 64/128)
Modulation coding schemes	from BPSK 1/2 to QAM64 5/6
Transmit power	up to 23 dBm
Receiver sensitivity	down to -93 dBm
Frequency range	3400-3700 MHz
Channel width	0.875*, 1.25*, 1.75*, 2.5*, 3.5, 5, 6, 7, 10, 12, 14, 15, 20, 28, 30, 40 MHz
Center frequency adjustment step	125 kHz
Duplex scheme	TDD
Wired Interfaces	1x GigabitEthernet (RJ45)

* available in select markets only



InfiMAN 2x2 R5000-0mxb/35.300.2x200

Consumption	up to 20 W				
Power options	110-240 VAC @ 50/60 Hz, ±43..56 VDC				
Outdoor Unit (ODU)	240 x 240 x 57 mm, 2.2 kg				
					
Part Number Options	Prefix	Freq. Band	Bitrate	Output Power	Capacity
	<i>R5000-0mxb</i>	<i>35</i>	<i>300</i>	<i>2x200</i>	<i>300</i>
Part Number Example	R5000-0mxb/35.300.2x200				
Packing List	<ul style="list-style-type: none"> - Outdoor unit R5000-0mxb/35.300.2x200 - 1 pcs. - Power Supply IDU-BS-G - 1 pcs. - Power Cord - 1 pcs. - Connector - 1 pcs. - Standard RJ-45 connector - 1 pcs. - Shielded RJ-45 connector - 1 pcs. - RJ-45 Plug Cap - 1 pcs. - MONT-KIT-85 Mounting kit - 1 pcs. - Quick Start Guide - 1 pcs. 				



InfiMAN 2x2 R5000-0mxb/35.300.2x200

Features

RADIO

- ▶ Voice/RTP Aware Superpacketting
- ▶ DFS
- ▶ Automatic Bitrate Control
- ▶ Automatic Transmit Power Control
- ▶ Automatic Distance Learning
- ▶ Channel Time Adjustment
- ▶ Spectrum Analyzer mode
- ▶ Channel testing tools

NETWORKING

- ▶ Ethernet-over-IP and IP-over-IP tunneling
- ▶ ARP protocol support
- ▶ MAC/IP filtering
- ▶ Full-fledged 2nd layer switch
- ▶ RIPv2 / OSPFv2 /static routing
- ▶ L2/L3 Firewall
- ▶ NAT (multipool, H.323-aware)
- ▶ DHCP client/server/relay

MANAGEMENT FEATURES

- ▶ Various Management Protocols: HTTP, HTTPS, Telnet, SSH, SNMP v1/2c/3 (MIB-II and proprietary MIBs)
- ▶ Graphical User Interface
- ▶ LED Indication: power status, wireless and wired link status, signal level
- ▶ Antenna alignment tool
- ▶ Automatic software update
- ▶ Online monitoring with proprietary EMS InfiMONITOR.

QUALITY-OF-SERVICE

- ▶ 17 priority queues
- ▶ IEEE 802.1p support
- ▶ IP TOS / DiffServ support
- ▶ Full voice support
- ▶ Traffic limiting (absolute, relative, mixed)
- ▶ Traffic redirection



InfiMAN 2x2 R5000-Omxb/35.300.2x200

Features

ENVIRONMENTAL

- ▶ **Outdoor Units:**
 - operating temperature range -40..+60 °C, (can be extended to -55..+60 °C, models with "t" index in PN), 100% humidity, condensing
 - IP66/IP67 compliant water and dust protection
 - wind load: 200 kph, survival
- ▶ **Indoor Unit:**
 - 0..+40 °C, 95% humidity, non-condensing

SECURITY FEATURES

- ▶ **Storm/flood protection**
- ▶ **Password protection**
- ▶ **Secure command-line access via SSH protocol**

MAC

- ▶ **ARP support**
- ▶ **Proactive channel testing**
- ▶ **Pseudo-radio interface:**
 - unique Infinet Wireless feature to join Infinet networks via 3rd party equipment
- ▶ **Automatic over-the-air firmware upgrade**

STANDARD COMPLIANCE

- ▶ **Radio**
 - EN 301 893 v.2.1.1
 - EN 302 502 v.2.1.1
 - FCC part 15.247
- ▶ **EMC**
 - EN 301 489-1
 - EN 301 489-17
 - FCC Part 15 Class B
- ▶ **Safety**
 - ETSI EN 60 950-1:2006
- ▶ **RoHS**
 - Directive 2011/65/EU

