


InfiLINK XG Um/6X.500.2x500

| | |
|---|--|
| Description | InfiLINK XG Um/6X.500.2x500, 6 GHz point-to-point unit, net throughput up to 500 Mbps, 2x N-type (F) connectors for external antenna |
| Net throughput | up to 500 Mbps |
| Recommended distances | up to 100 km |
| Radio technology | MIMO 2x2, Cyclic single carrier |
| Modulation coding schemes | from QPSK 1/4 to QAM1024 8/10 |
| Transmit power | up to 27 dBm |
| Receiver sensitivity | down to -92 dBm |
| Frequency range | 6000-6425 MHz |
| Channel width | 10, 20, 40 MHz |
| Center frequency adjustment step | 1 MHz |
| Duplex scheme | TDD |
| Wired Interfaces | 2x GigabitEthernet, SFP |



InfiLINK XG Um/6X.500.2x500

| | |
|--------------------|---|
| Consumption | up to 30 W |
| Power options | 90-240 VAC @ 50/60 Hz, 43..56 VDC |
| Outdoor Unit (ODU) | 256 x 240 x 86 mm, 2.1 kg |
| |  |
| Packing List | <ul style="list-style-type: none"> - Outdoor unit Um/6X.500.2x500 - 1 pcs. - Power Supply IDU-CPE-G(56W) - 1 pcs. - Power Cord - 1 pcs. - Cable Gland for RJ-45 - 2 pcs. - Cable Gland for optical cable - 1 pcs. - Standard RJ-45 connector - 2 pcs. - Shielded RJ-45 connector - 1 pcs. - RJ-45 Plug Ca |



InfiLINK XG Um/6X.500.2x500

Features

RADIO

- ▶ **Best-in-breed spectral efficiency**
 - up to 12,5 bps/Hz
 - real throughput in excess of 130 Mbps in just 10 MHz of spectrum
- ▶ **High transmit power and perfect sensitivity even at the highest-order modulations**
 - Reliable signal receiving in both LOS and NLOS conditions
- ▶ **TDD synchronization using a built-in GNSS receiver**

NETWORKING

- ▶ **Built-in full-fledged L2 switch supporting VLAN and STP**
- ▶ **Transparent L2 transport for Ethernet traffic of any type**

MANAGEMENT FEATURES

- ▶ **Web-based graphical user interface**
- ▶ **Command line interface**
- ▶ **SNMP v1/2c/3 support (MIB-II and proprietary MIBs)**
- ▶ **Centralized monitoring using EMS InfiMONITOR.**

QUALITY-OF-SERVICE

- ▶ **QoS support:**
 - 4 priority queues: strict and weighted prioritisation
 - Classification based on IEEE 802.1p
 - Egress rate limiting on each network port

INSTALLATION AND DIAGNOSTIC TOOLS

- ▶ **LED indication**
 - power status
 - wired and wireless link status
 - received signal strength indication
 - TDD sync status
- ▶ **Web GUI tools**
 - antenna alignment tool
 - spectrum analyzer



InfiLINK XG Um/6X.500.2x500

Features

ENVIRONMENTAL

- ▶ **Outdoor Units:**
 - operating temperature range -40..+60 °C, (can be extended to -55..+60 °C, models with "t" index in PN), 100% humidity, condensing
 - IP66/IP67 compliant water and dust protection
 - wind load: 200 kph, survival
- ▶ **Indoor Unit:**
 - 0..+40 °C, 95% humidity, non-condensing

STANDARD COMPLIANCE

- ▶ **Safety:**
 - EN 60950-1:2006, UL 60950-1 2nd ed.
- ▶ **Radio (pending):**
 - EN 302 326-2
- ▶ **EMC:**
 - ETSI EN 301 489-1, ETSI EN 301 489-17, FCC Part 15 Class B
- ▶ **RoHS:**
 - Directive 2011/65/EU

